

## ***Section VI. Schedule of Requirements***

The delivery schedule expressed as weeks/months stipulates hereafter a delivery date which is the date of delivery to the project site.

<b>Item No.</b>	<b>Description</b>	<b>Qty.</b>	<b>Unit</b>	<b>Delivered, Weeks/Months</b>
1	<b>BRANDED DESKTOP COMPUTER</b> <ul style="list-style-type: none"> <li>- Display: 24- inch 1920x1080 resolution</li> <li>- Processor: Intel Core i7 13th Gen (16cores, 24 threads, up to 5.2 Ghz turbo boost)</li> <li>- Memory: 16GB DDR4</li> <li>- Storage: 512 M.2</li> <li>- Graphics: Dedicated 4GB NVIDIA DDR6</li> <li>- Network: 802.11 ax/ac/a/bg/n, Lan 10/100/100, Wifi 6 and Bluetooth 5.2</li> <li>- Operating System: Windows 11</li> <li>- Mouse: Wired mouse</li> <li>- Keyboard: Wired Keyboard</li> <li>- Webcam: 1080p Branded webcam</li> <li>- Audio: Branded wired Headset with noise cancelling</li> <li>- AVR: Automatic Voltage Regulator AVR Power Supply Surge Protection 1000VA/500W</li> </ul>	16	unit	Thirty (30) Calendar Days
	<b>UNINTERRUPTIBLE POWER SUPPLY (UPS)</b> <ul style="list-style-type: none"> <li>- UPS Floating</li> <li>- Charging Voltage: 13.5-13.8V</li> <li>- Type: 12V/7Ah x1</li> <li>- Typical battery runtime</li> <li>- IT Load (100W): 18 min</li> <li>- Recharge time: 4-6 hours recover to 90% capacity</li> <li>- 50% load: 5 min</li> <li>- 75% load: 1.5 min</li> <li>- On/Off switch: Yes</li> <li>- Indicator: LED</li> <li>- Communication-USB: No</li> <li>- Communication-RS232: No</li> <li>- RJ11 protection: No</li> <li>- Rating (VA/W): 700VA/360W</li> <li>- Format: Tower</li> <li>- Input voltage range: 140-300 VAC</li> <li>- Frequency range: 60/50 Hz (Auto sensing) Surge protection</li> <li>- Generator compatible</li> <li>- Mute by power key</li> </ul>	20	unit	Thirty (30) Calendar Days



	<ul style="list-style-type: none"> <li>- Circuit breaker</li> <li>- Output voltage: 230 VAC</li> <li>- Output voltage reg. (Battery mode): <math>\pm 10\%</math></li> <li>- Battery wave form: Stepped sine wave</li> <li>- Protection: PCBA current sensor (F/W protection)</li> <li>- Output backup socket: DIN model: (2) Schuko outlets NEMA model: (4) NEMA Universal outlets UNI model: (2) Universal outlets</li> <li>- Transfer time: 2-6ms typical, 10ms max</li> </ul>			
***** Nothing Follows*****				

I hereby verify to comply with all the above requirements.

\_\_\_\_\_  
Signature over printed name of the authorized representative

\_\_\_\_\_  
Company name

\_\_\_\_\_  
Date