

## ***Section VII. Technical Specifications***

### **Notes for Preparing the Technical Specifications**

A set of precise and clear specifications is a prerequisite for Bidders to respond realistically and competitively to the requirements of the Procuring Entity without qualifying their Bids. In the context of Competitive Bidding, the specifications (*e.g.* production/delivery schedule, manpower requirements, and after-sales service/parts, descriptions of the lots or items) must be prepared to permit the widest possible competition and, at the same time, present a clear statement of the required standards of workmanship, materials, and performance of the goods and services to be procured. Only if this is done will the objectives of transparency, equity, efficiency, fairness, and economy in procurement be realized, responsiveness of bids be ensured, and the subsequent task of bid evaluation and post-qualification facilitated. The specifications should require that all items, materials and accessories to be included or incorporated in the goods be new, unused, and of the most recent or current models, and that they include or incorporate all recent improvements in design and materials unless otherwise provided in the Contract.

Samples of specifications from previous similar procurements are useful in this respect. The use of metric units is encouraged. Depending on the complexity of the goods and the repetitiveness of the type of procurement, it may be advantageous to standardize the General Technical Specifications and incorporate them in a separate subsection. The General Technical Specifications should cover all classes of workmanship, materials, and equipment commonly involved in manufacturing similar goods. Deletions or addenda should then adapt the General Technical Specifications to the particular procurement.

Care must be taken in drafting specifications to ensure that they are not restrictive. In the specification of standards for equipment, materials, and workmanship, recognized Philippine and international standards should be used as much as possible. Where other particular standards are used, whether national standards or other standards, the specifications should state that equipment, materials, and workmanship that meet other authoritative standards, and which ensure at least a substantially equal quality than the standards mentioned, will also be acceptable. The following clause may be inserted in the Special Conditions of Contract or the Technical Specifications.

### **Sample Clause: Equivalency of Standards and Codes**

Wherever reference is made in the Technical Specifications to specific standards and codes to be met by the goods and materials to be furnished or tested, the provisions of the latest edition or revision of the relevant standards and codes shall apply, unless otherwise expressly stated in the Contract. Where such standards and codes are national or relate to a particular country or region, other authoritative standards that ensure substantial equivalence to the standards and codes specified will be acceptable.

Reference to brand name and catalogue number should be avoided as far as possible; where unavoidable they should always be followed by the words "*or at least equivalent.*" References to brand names cannot be used when the funding source is the GOP.

Where appropriate, drawings, including site plans as required, may be furnished by the Procuring Entity with the Bidding Documents. Similarly, the Supplier may be requested to provide drawings or samples either with its Bid or for prior review by the Procuring Entity during contract execution.

Bidders are also required, as part of the technical specifications, to complete their statement of compliance demonstrating how the items comply with the specification.

# Technical Specifications

Item No.	Specification	Statement of Compliance
		<p><i>[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.]</i></p>
1	<p><b>AI Supercomputer for Embedded and Edge Systems</b> (AI Supercomputer for Embedded and Edge Systems) (GPU: NVIDIA Volta Architecture with 384 NVIDIA CUDA cores and 48 Tensor Cores            CPU: 6-core NVIDIA Carmel ARM v 8.2 64-bit CPU 6 MB L2+4 MBL3            DLA: 2x NVDLA Engines            Memory: 8 GB 128-bit LPDDR4x51.2 GB/s            Storage: microSD            Camera: 2x MIPI CSI-2 D-PHY lanes            Connectivity: Gigabit Ethernet, M.2 Key E (WiFi/BT included), M.2 Key M (NVMe)            Display: HDMI and DP            USB: 4 x USB 3.1, USB 2.0 Micro-B Others: GPIOs, I2C, I2S, SPI, UART Mechanical: 103 mm x 90.5 mm x 34 mm )</p>	

7

2	<p><b>Depth Camera</b> (Use environment: Indoor/Outdoor Image Sensor Technology: Global Shutter Ideal range: .3 m to 3 m Depth technology: Stereoscopic Depth Field of View (FOV): 87° x 58° Minimum depth distance (Min-Z) at max resolution:~28 cm Depth Output Resolution: Up to 1280 x 720 Depth Accuracy: &lt;2% at 2 m Depth frame rate: Up to 90 fps RGB frame resolution: 1920 x 1080 RGB Sensor FOV (H x V): 69° x 42° RGB frame rate: 30 fps RGB sensor resolution: 2 MP RGB sensor technology: Rolling Shutter Camera Module: Intel RealSense Module D430 + RGB Camera Vision processor board: Intel RealSense Vision Processor D4 Form Factor: Camera Peripheral Connectors: USB-C* 3.1 Gen 1* Length x Depth x Height 90 mm x 25 mm x 25 mm Mounting mechanism: -One 1/4 -20 UNC thread mounting point -Two M3 thread mounting points )</p>	
3	<p><b>IP Camera</b> (Camera Image Sensor: 1/ 2.5” Progressive Scan CMOS Shutter Speed 1/3 s to 1/100,000 s Day and Night: IR Cut Filter Lens Focus: Fixed Lens Type: 2.8/4/6/8 mm Video Max. Resolution: 3840 x 2160 Main Stream: 50 Hz: 12.5 fps (3840 x 2160), 20 fps (3072 x 1728), 25 fps (2560 x 1440, 1920 x 1080, 1280 x 720), 60 Hz: 15 fps (3840 x 2160), 20 fps (3072 x 1728), 30 fps (2560 x 1440, 1920 x 1080, 1280 x 720) Network: Simultaneous Live View: Up to 6 channels User/Host: Up to: 32 users, 3 levels: Administrator, Operator and User Network Storage: Support Micro SD/SDHC/SDXC card (128G), local storage and NAS (NFS, SMB/CIFS) Image Day/Night Switch: Day/Night/Auto/Schedule )</p>	
4	<p><b>Laptop</b> (Processor: Up to 11th Gen. Intel® Core™ i7 Operating System: Windows 10 (Free upgrade to Windows 11* when available) Display: 17.3” FHD (1920 x 1080), 240 Hz, IPS-level Chipset: Intel HM570 Graphics: NVIDIA® GeForce RTX™ 3070 GPU 8 GB DDR6 Memory: 16 GB DDR4 3200 MHz Storage: 2TB NVMe PCIe Gen3x4 SSD Webcam: HD Type (30fps @720p) Keyboard: Per-Key RGB Backlight Keyboard Communication: Gb LAN (up to 2.5G) Killer ax Wi-Fi 6E + Bluetooth v5.2 Audio Jack: 1x Mic-in/Headphone-out Combo Jack I/O Ports: 3x Type-A USB3.2 Gen1 1x RJ45 1x (8k @60</p>	

	Hz/4K @ 120 Hz) HDMI 1x Mini-Display Port Battery: 4-Cell 65 Battery (Whr) Dimension (WXDXH): 397 mm x 284 mm x 25.9 mm Weight (With Battery) : 2.9 kg Color: Core Black )	
5	<b>Multi-Imager Panoramic Dome Camera</b> (Panoramic Camera Up to 8 MP Resolution (4 X 2 MP Sensors) Image Sensor: 1/1.8" Progressive Scan CMOS 4x5 mm Fixed Lenses 180° Horizontal View (Stitched Image) Ultra-Low Light, Slow Shutter 1 Edge Storage MicroSD Slot, 128 GB 24 VAC/PoE+ (802.3at) Audio/Alarm I/O IP66 and IK10 Protection Heater and Fan )	
<b>***** Nothing Follows*****</b>		

*Additional Requirements:*

*The technical specification that shall be submitted by the Bidder shall include, among others:*

- a. product specifications as supported by brochures or catalogues.*