



University of Science and Technology of Southern Philippines

Alubijid | Cagayan de Oro | Claveria | Jasaan | Oroquieta | Panaon

INVITATION /REQUEST FOR SUBMISSION OF PRICE QUOTATION
Posted in PhilGEPS Webstie/Conspicuous Place at the Procuring Entity

The University of Science & Technology of Southern Philippines, through the Bids and Awards Committee (BAC) hereby invites interested parties to submit quotation for the procurement of the following item:

Reference No	Qty.	Unit	Specification/Description	Budget for the Contract	Mode of Procurement
RFQ-NP-SVP-547a-2021	Please see details below	Please see details below	Negotiated Procurement for the Supplies and Materials Semi-Expendable 1	₱56,610.00	Small Value Procurement-Section 53.9, Rule XVI, Revised IRR of RA 9184)

Deadline for the submission of quotation is on October 7, 2021 at 12:00 noon at the Procurement Unit, 2nd Floor, USTP Gymnasium building. You may submit your quotation through fax number 856-4696 / 856-1739 or through personal delivery in a sealed envelope.

The University of Science & Technology of Southern Philippines reserves the right to accept or reject any or all bids / price quotations, to annul the process, and to reject all bids at any time prior to contract award, without thereby incurring any liability to the affected bidder or bidders.


ATTY. KENNETH M. KEMPIS
BAC II Chairman



University of Science and Technology of Southern Philippines
Alubijid | Cagayan de Oro | Claveria | Jasaan | Oroquieta | Panaon

Date: October 01, 2021
Quotation No.: RFQ-NP-SVP-547a-2021

Name of Project: Procurement of Supplies and Materials Semi-Expendable 1

The Manager

Cagayan de Oro City

Please quote your lowest price on the item/s listed below, subject to the general Conditions stated below, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than October 7, 2021 at 12:00 noon. Please enclosed in a sealed envelope.

Kenneth M. Kempis
ATY. KENNETH M. KEMPIS

BAC II Chairman

- NOTE:
1. DELIVERY PERIOD WITHIN 7 CALENDAR DAYS UPON RECEIPT OF PO.
 2. PRICE VALIDITY SHALL BE FOR A PERIOD OF 30 CALENDAR DAYS
 3. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATIONS OF THE PRODUCT BEING OFFERED. (if applicable)
 4. THE USTP RESERVES THE RIGHT TO REJECT ANY OR ALL BIDS FOR ANY JUSTIFIABLE AND REASONABLE GROUND WHERE THE AWARD OF THE CONTRACT WILL NOT REDOUND TO THE BENEFIT OF THE GOP.
 5. REQUIREMENTS: 1) PHILGEPS REGISTRATION (PLATINUM MEMBERSHIP).

ITEM #	QTY	UNIT	DESCRIPTIONS AND SPECIFICATIONS	APPROVED UNIT COST (php)	UNIT PRICE
1	1	unit	600W Fixed Installation DC-AC Power Inverter, 24V dc / 230V ac (Stock No.: 174-8095) (Input Voltage 24V dc Output Voltage 230V ac Output Power Continuous 600W Output Power Waveform Modified Sine Wave Output Connection Type Schuko Socket Efficiency 85% MTBF 100kh Output Current 2.6A Length 210mm Width 173mm Depth 65mm Minimum Temperature 0°C Number of Output Connections 1 Output Frequency Range 50Hz Maximum Input Current 30A dc Mounting Type Screw Mount Inverter Directionality DC to AC Maximum Temperature +40°C)	3,500.00	
2	5	meter	Aluminum wire mesh (Hole size of mesh is approx :Fine: 1x2mm) (Feature: -100% new and high quality. -Anti-acid, anti-alkali, high temperature, tensile and wear resistance. -Structure closely, evenly distributed wire, not easy to move. -Made of high-quality metal, strong and durable, strong load-bearing capacity. -Surface rust treatment, do not discoloration, not rust.)	300.00	
3	10	unit	Brass Ball Valve 1/2 in BSPP 2 Way (Stock No.: 733-5139) (Attachment Type Threaded Threaded Connection 1/2 in BSPP Body Material Brass Thread Size 1/2 in Safe for Use With Air, Oil, Steam, Water Maximum Working Pressure 50 bar Connection Size mm 12.7mm Connection Size inch 1/2 in Type 2 Way)	560.00	
4	10	unit	Elbow Male Hose Coupling, Push-On, POM (Stock No.: 795-499) (Hose Inner Diameter 12mm Body Material POM Threaded Connection Push-On Coupling Gender Male Coupling Connector Direction Elbow Series WS)	170.00	
5	20	pc	Empty Blue Round Water Container 18 Liters/5 gallon ()	200.00	
6	3	unit	Heating Element (Stock No.: 725-6499) (Self regulating PTC heater Protection Class II Lead wire silicone, UL 3135, white, AWG 20, Length = 100±5mm Termination 6mm splice crimp)	1,300.00	
7	75	unit	Mild Steel Hex Screw Worm Drive, 20mm Band Width, 13mm - 20mm Inside Diameter (Stock No.: 145-0245) ((Hose Inner Diameter 12.5mm Hose Outer Diameter 17.5mm))	20.00	
8	2	unit	Nito Straight Brass Hose Connector (Male and Female Adaptor set) (Stock No.: 330-0599) ((Hose Inner Diameter 12.5mm Hose Outer Diameter 17.5mm))	500.00	

9	2	roll	PET, PVC Flexible Tubing, Transparent, 17.5mm External Diameter, 25m Long Reinforced, 60mm Bend Radius, (Stock No.: 368-0211) ((Hose Inner Diameter 12.5mm Hose Outer Diameter 17.5mm))	3,100.00	
10	1	length	PVC pipe- 4 inches Diameter sch 40x 20ft length ((Hose Inner Diameter 12.5mm Hose Outer Diameter 17.5mm))	1,100.00	
11	3	unit	Reliance 3bar Pressure Relief Valve With Female BSP 1/2 in BSP Female Connection and a BSP 1/2 Exhaust Port (Reliance 3bar Pressure Relief Valve With Female BSP 1/2 in BSP Female Connection and a BSP 1/2 Exhaust Port (Stock No.: 211-0430) ((Connection 1/2 in BSP Female Maximum Set Pressure 3bar Maximum Temperature +140°C For Use With Hot Water Exhaust Port Size BSP 1/2 Body Material Brass Connection Gender Female Thread Size 1/2 in Thread Standard or Connection Type BSP)	1,700.00	
12	70	unit	Straight Brass Hose Connector, 1/2 in BSP Male (Stock No.: 176-2042) (Attachment Type Threaded Threaded Connection 1/2 in BSP Body Material Brass Thread Size 1/2 in Safe for Use With Air, Oil, Steam, Water Maximum Working Pressure 50 bar Connection Size mm 12.7mm Connection Size inch 1/2 in Type 2 Way)	230.00	
13	10	unit	Straight Male Hose Coupling, Push-On, POM (Stock No.: 795-376) ((Hose Inner Diameter 12mm Body Material POM Threaded Connection Push-On Coupling Gender Male Coupling Connector Direction Straight Series GS)	115.00	
14	2	unit	Transparent Sealant Non-Slump Paste 300 ml Cartridge, water proof (Stock No.: 341-0961) ()	750.00	
15	10	unit	White PTFE Tape 12mm x 12m x 0.075mm (Stock No.: 183-3490) ((Made from PTFE (polytetrafluoroethylene) • Non-adhesive • Operating temperature range of -200°C to +260°C • Length of 12 m • Width of 12 mm • Thickness of 0.075 mm)	96.00	
16	10	unit	Y Male Hose Coupling Y Coupler, Push-On, POM (Stock No.: 795-556) (Hose Inner Diameter 12mm Coupling Connector Type Y Coupler Body Material POM Threaded Connection Push-On Coupling Gender Male Coupling Connector Direction Y Series YS)	180.00	

Magomnang-Power Inverte-
RFQ-NP-SVP-547a-2021
Resolution No. 644 s. 2021
PR No.-202109-607

_____ Date

C. M. Recte Avenue, Lapasan, Cagayan de Oro City 9000 Philippines, Tel. Nos. +63 (88) 856 1738; Telefax +63 (88) 856 4696 | www.ustp.edu.ph

handwritten signature