




INVITATION /REQUEST FOR SUBMISSION OF PRICE QUOTATION
Posted in PhilGEPS Website/Conspicuous Place at the Procuring Entity

The University of Science & Technology of Southern Philippines, through the Bids and Awards Committee (BAC) hereby invites interested parties to submit quotation for the procurement of the following item:

Reference No.	Qty.	Unit	Specification/Description	Budget for the Contract	Mode of Procurement
RFQ-NP-SVP-636a-2021	Please see details below	Please see details below	Negotiated Procurement for the Supplies and Materials	₱136,000.00	Small Value Procurement- Section 53.9, Rule XVI, Revised IRR of RA 9184)

Deadline for the submission of quotation is on November 04, 2021 at 12:00 noon at the Procurement Unit, 2nd Floor, USTP Gymnasium building. You may submit your quotation through fax number 856-4696 / 856-1739 or through personal delivery in a sealed envelope.

The University of Science & Technology of Southern Philippines reserves the right to accept or reject any or all bids / price quotations, to annul the process, and to reject all bids at any time prior to contract award, without thereby incurring any liability to the affected bidder or bidders.


ATTY. KENNETH M. KEMPIS
BAC II Chairman



Date: October 29, 2021
 Quotation No.: RFQ-NP-SVP-636a-2021

Name of Project: Procurement of Supplies and Materials

The Manager

Cagayan de Oro City

Please quote your lowest price on the item/s listed below, subject to the general Conditions stated below, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than November 02, 2021 at 12:00 noon. Please enclosed in a sealed envelope.

Kenneth M. Kempis
 ATTY. KENNETH M. KEMPIS
 BAC II Chairman

- NOTE:
1. DELIVERY PERIOD WITHIN 7 CALENDAR DAYS UPON RECEIPT OF PO.
 2. PRICE VALIDITY SHALL BE FOR A PERIOD OF 30 CALENDAR DAYS
 3. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATIONS OF THE PRODUCT BEING OFFERED. (if applicable)
 4. THE USTP RESERVES THE RIGHT TO REJECT ANY OR ALL BIDS FOR ANY JUSTIFIABLE AND REASONABLE GROUND WHERE THE AWARD OF THE CONTRACT WILL NOT REDOUND TO THE BENEFIT OF THE GOP.
 5. REQUIREMENTS: 1) PHILGEPS REGISTRATION (PLATINUM MEMBERSHIP).

ITEM #	QTY	UNIT	DESCRIPTIONS AND SPECIFICATIONS	APPROVED UNIT COST (php)	UNIT PRICE
1	1	unit	Imaging Moisture Meter, Maximum Measurement 100% Maximum Measurement: 100%; Best Accuracy: ±5 %; Display Type: Digital; Power Source: Battery; Battery Type: Rechargeable Li-Ion; Battery Life: 18 h; Model Number: MR160; moisture meter is equipped with a pinless moisture sensor and pin probe to provide the flexibility of non-intrusive or intrusive measurements. It has a built-in thermal camera with infrared guided measurement (IGM) technology to quickly scan and target moisture issues. It is made of impact-resistant plastic with a large LCD. Supplied with Li-ion battery (x2); Portable, tough and durable Troubleshoot quickly; External pin probe included for contact moisture measurements; Easy targeting with a laser pointer and display cross-hairs; Document thermal images and moisture readings on one screen; Review images and generate reports with free FLIR tools software; Internal rechargeable battery with USB; Power source battery type.	58,000.00	
2	1	unit	K Input Wired Digital Thermometer (Absolute Maximum Temperature Measurement +1300 °C, +1999°F Thermometer TypeWired Probe TypeK Best Accuracy±0.2 Reading +1°C % Number of Temperature Inputs1 Resolution0.1 °C, 0.2 °F Length74mm Width39mm Height170mm Minimum/Maximum RecordingsYes Weight 430g Model Number pRS51 Battery Type 9V Temperature ScaleCentigrade	9,000.00	
3	1	unit	Laser Measure, 0.1 → 50m Range, ±1.5 mm Accuracy (Accuracy:±1.5 mm Measurement Range:0.1 → 50m Imperial or Metric:Imperial, Metric Display TypeDigital Metric-Imperial ConversionYes Model Number pTLM165	13,000.00	
4	1	unit	Table top pH Meter (-2 to +16 pH) Maximum pH: +16pH; Minimum pH: -2pH; pH Resolution: 0.01pH; Best pH Accuracy: ±0.01pH; Maximum Temperature Measurement: +120 °C; Minimum Temperature Measurement: -9.9°C; Temperature Measurement Resolution: 0.1°C; Best Temperature Measurement Accuracy: ±0.5 °C; Maximum Oxidation Reduction Potential:+2000 mV, +399.9 mV; Minimum Oxidation Reduction Potential: -2000 mV, -399.9 mV; Maximum Operating Temperature: +50°C; Plug Type:Type C - European Plug; Oxidation Reduction Potential Range: ±2000 mV, ±399.9 mV; Model Number: PH211; ; Height: 74mm; Minimum Operating Temperature: 0°C; Weight: 1.1kg; Oxidation Reduction Potential Accuracy:±0.2 mV, ±1 mV; Dimensions: 240 x 182 x 74mm; Length: 240mm; Best Oxidation Reduction Potential Resolution: 0.1mV; Width:182mm.	50,000.00	

5	1	unit	Tachometer Best Accuracy $\pm 0.05\% + 1$ digit - Contact, Non Contact LCD (Best Accuracy $\pm 0.05\% + 1$ digit Category Contact, Non Contact Battery Type 9V Display Type LCD Dimensions 60 x 42 x 160mm Weight 160g Height 160mm Length 60mm Width 42mm	6,000.00	
---	---	------	---	----------	--

Price Validity:

After having carefully read and accepted for General Conditions, I/We quote on the item at prices

noted above.

Magomnang-Duplex Scanner
RFQ-NP-SVP-636a-2021
Resolution No. 745 s. 2021
PR No.-202110-705

C.M. Recto Avenue, Lapasan, Cagayan de Oro City 9000 Philippines, Tel. Nos. +63 (88) 856 1738; Telefax +63 (88) 856 4696 | www.ustp.edu.ph

Tel. #/address/e-mail add

Date

Handwritten signature