

University of Science and Technology of Southern Philippines

Alubijid | Cagayan de Oro | Claveria | Jasaan | Oroquieta | Panaon

INVITATION /REQUEST FOR SUBMISSION OF PRICE QUOTATION Posted in PhilGEPS Webstie/Conspicuous Place at the Procureing Entity

The University of Science & Technology of Southern Philippines, through the Bids and Awards Committee (BAC) hereby invites interested parties to submit quotation for the procurement of the following item:

Reference No	. Qty.	Unit	Specification/Description	Budget for the Contract	Mode of Procurement
RFQ-NP- SVP-766- 2022	600	Please see details below	Negotiated Procurement for the Calibration Equipment and Accessories	₱350,000.00	Small Value Procurement- Section 53.9, Rule XVI, Revised IRR of RA 9184)

Deadline for the submission of quotation is on September 23, 2022 at 12:00 noon at the Procurement Unit, 2nd Floor, USTP Gymnasium building. You may submit your quotation through fax number 856-4696 / 856-1739 or through personal delivery in a sealed envelope.

The University of Science & Technology of Southern Philippines reserves the right to accept or reject any or all bids / price quotations, to annul the process, and to reject all bids at any time prior to contract award, without thereby incurring any liability to the affected bidder or bidders.

(sgd.)
ATTY. JONATHAN S. OCHE
BAC I Chairman

University of Science and Technology of Southern Philippines

Alubijid | Cagayan de Oro | Claveria | Jasaan | Oroquieta | Panaon

Data:	September	20	2022
Date.	September	ZU.	ZUZZ

Quotation No.: RFQ-NP-SVP-766-2022

Name of Project: Procurement of the Calibration Equipment and Accessories

Cagayan de Oro City

Please quote your lowest price on the item/s listed below, subject to the general Conditions stated below, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than <u>September 23, 2022 at 12:00 noon</u>. Please enclosed in a sealed envelope.

(sgd.)
ATTY. JONATHAN S. OCHE
BAC I Chairman

NOTE:

- 1. DELIVERY PERIOD WITHIN 7 CALENDAR DAYS UPON RECEIPT OF PO.
- 2. PRICE VALIDITY SHALL BE FOR A PERIOD OF 30 CALENDAR DAYS
- 3. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATIONS OF THE PRODUCT BEING OFFERED. (if applicable)
- 4.THE USTP RESERVES THE RIGHT TO REJECT ANY OR ALL BIDS FOR ANY JUSTIFIABLE AND RESOANABLE GROUND WHERE THE AWARD OF THE CONTRACT WILL NOT REDOUND TO THE BENEFIT OF THE GOP.
- 5. REQUIREMENTS: 1) PHILGEPS REGISTRATION (PLATINUM MEMBERSHIP).

ITEM#	QTY	UNIT	DESCRIPTIONS AND SPECIFICATIONS	APPROVED UNIT COST (php)	UNIT PRICE
1	1	set	750P01 Pressure Module, For Use With 725, 726, 750 Series (0.025% reference uncertainty 6-month and 1-year specifications Temperature compensated 0°C to 50°C Digital communication to calibrators, no analog losses or errors Broad selection of ranges Gauge, differential, dual range, absolute and vacuum measurement models Urethane over moulding protection)	140,000.00	
2	1	set	Hand Hydraulic Pressure Pump Kit 690bar (Premium 700HTPK-2 hydraulic pressure test kit The Hand Hydraulic Pressure Pump Kit 690bar can be used in a wide range of industrial applications and systems. The test kit is the ideal instrument for technicians and specialist engineers to carry out essential testing, maintenance, and calibration procedures. Some of the most common are • Pressure switches • Pressure Indicators • Controllers)	130,000.00	
3	1	unit	True RMS Wireless Display Digital Multimeter (Wireless technology allows the display to be carried up to 10 m away from the point of measurement for added flexibility The removable magnetic display can be conveniently mounted where it is easily seen Measurements can be made without holding the meter to improve visual focus on probes and augment safe electrical measurements Low-power 802.15.4 wireless technology does not interfere with measurement accuracy Use as a conventional multimeter when the display is connected Radio transmitter automatically turns off when the display is connected to the meter True RMS ac voltage and current for accurate measurements on non-linear signals Min/Max and average recording to capture variations automatically Resistance, continuity and diode test K Type temperature measurement range Easy-to-read display with large digits and bright backlight Auto power off maximises battery life Safety rating CAT IV 600 V, CAT III 1000 V)	50,000.00	
4	1	unit	Type K Surface Temperature Probe (Specifications Sensor Type: Type K Probe Type: Surface Probe Length: 322.6mm Probe Diameter: 22.9mm Maximum Temperature Measurement: +600 °C Cable Length: 1m Best Accuracy: ±1.2 % Connector Type: Miniature Plug Model Number: 80PK-27)	30,000.00	

Delivery Period:

Price Validity:

After having carefully read and accepted for General Conditions, I/We quote on the item at prices noted above.

Tel. #./address/e-mail add