



University of Science and Technology of Southern Philippines

Alubijid | Cagayan de Oro | Claveria | Jasaan | Oroquieta | Panaon

INVITATION /REQUEST FOR SUBMISSION OF PRICE QUOTATION
Posted in PhilGEPS Webstie/Conspicuous Place at the Procureing Entity

The University of Science & Technology of Southern Philippines, through the Bids and Awards Committee (BAC) hereby invites interested parties to submit quotation for the procurement of the following item:

Reference No.	Qty.	Unit	Specification/Description	Budget for the Contract	Mode of Procurement
RFQ-NP-SVP-re-169-2022	Please see details below	Please see details below	Negotiated Procurement of the Disaster Risk Reduction Project	₱450,000.00	Small Value Procurement- Section 53.9, Rule XVI, Revised IRR of RA 9184)

Deadline for the submission of quotation is on June 10, 2022 at 12:00 noon at the Procurement Unit, 2nd Floor, USTP Gymnasium building. You may submit your quotation through fax number 856-4696 / 856-1739 or through personal delivery in a sealed envelope.

The University of Science & Technology of Southern Philippines reserves the right to accept or reject any or all bids / price quotations, to annul the process, and to reject all bids at any time prior to contract award, without thereby incurring any liability to the affected bidder or bidders.

sgd.
ATTY. JONATHAN S. OCHE
BAC I Chairman

University of Science and Technology of Southern Philippines

Alubijid | Cagayan de Oro | Claveria | Jasaan | Oroquieta | Panaon

Date: June 07, 2022

Quotation No.: RFQ-NP-SVP-re-169-2022

Name of Project: Procurement for the
Disaster Risk Reduction Project

The Manager

Cagayan de Oro City

Please quote your lowest price on the item/s listed below, subject to the general Conditions stated below, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than June 10, 2022 at 12:00 noon. Please enclosed in a sealed envelope.

sgd.
ATTY. JONATHAN S. OCHE
BAC I Chairman

- NOTE:
1. DELIVERY PERIOD WITHIN 7 CALENDAR DAYS UPON RECEIPT OF PO.
 2. PRICE VALIDITY SHALL BE FOR A PERIOD OF 30 CALENDAR DAYS
 3. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATIONS OF THE PRODUCT BEING OFFERED. (if applicable)
 4. THE USTP RESERVES THE RIGHT TO REJECT ANY OR ALL BIDS FOR ANY JUSTIFIABLE AND REASONABLE GROUND WHERE THE AWARD OF THE CONTRACT WILL NOT REDOUND TO THE BENEFIT OF THE GOP.
 5. REQUIREMENTS: 1) PHILGEPS REGISTRATION (PLATINUM MEMBERSHIP).

ITEM #	QTY	UNIT	DESCRIPTIONS AND SPECIFICATIONS	APPROVED UNIT COST (php)	UNIT PRICE
	1	lot	Radio Communication System	450,000.00	
RoIP Gateway (Radio over IP)					
	1	unit	1. IP Network Audio System Management Software 2. Center of IP network audio system and IP PA system. 3. Support Windows 2000, Windows 2008, Windows XP, Windows 7. 4. All equipment working status could be monitored and displayed on this software. 5. Flexible multiple level loudspeaker zone definitions, end-user can define loudspeakers into as many as possible zones at the same time. 6. Support max 5 different sound cards for simultaneously sources collection.	113,700.00	
VHF Base Radio					
	2	unit	1) Frequency coverage: TX: 144–148MHz, RX: 136–174MHz, TX/RX: 144–148MHz 2) Number of channels: 207 channels (including 6 scan edges, and 1 call) 3) Type of emission: F2D, F3E (FM) 4) Frequency stability: ±3ppm 5) Power supply requirement: 13.8V DC ±15% 6) Current drain (approx.) • Tx 65W: 11A • Rx Max. audio/Stand-by: 1.5A/0.4A 7) Antenna impedance: 50Ω (SO-239) 7) Operating temperature range: –10°C to +60°C; 14°F to +140°F 8) Dimensions (WxHxD; Projections not included): 140x40x162 mm; 5.51x1.57x6.38 in 9) Weight (approx.): 1.1 kg; 2.43lb	14,450.00	
Programming Cable					

1

2	pcs	PROG CABLE KIT 1. Computer Radio Interface Cables 2. PC Control Programming Cables 4. Computer/Radio Connector Type: RS-232 5. Remote Port Connector: Stereo 3.5mm male plug 6. D-Sub 25-pin ACC Cable	4,500.00	
Power Supply 30Amps				
2	pcs	30AMPS POWER SUPPLY BATT CHARGER 1. 220-240VAC Input 2. 12VDC Output 3. 30A	10,500.00	
VHF Portable Radio				
10	unit	1) Frequency range (TX/RX guaranteed range): 136–174 MHz, (EX Hi power TX: 144–160 MHz) 2) Type of emissions: F2D, F3E (FM, FM-N) 3) Number of channels: 200 channels 4) Antenna impedance: 50 Ω 5) Power supply requirement: 7.5 V DC 6) Operating temperature range: –20°C to +60°C, –4°F to +140°F 7) Frequency stability: ±2.5 ppm (–20°C to +60°C, –4°F to +140°F) 8) Current drain • TX (EX Hi/Hi/Mid/Low): 1.6/1.4/1.0/0.5 A typical • RX (Max. audio): 450 mA typ. (INT SP), 200 mA typ. (EXT SP) 8) Dimensions (W×H×D) (Projections not included): 58.6 × 112 × 30.5 mm, 2.3 × 4.4 × 1.2 in (with BP-298) 9) Weight (Approximate): 300 g, 10.6 oz	8,500.00	
1	lot	Roughing-ins, Installation Materials	60,000.00	
1	lot	Configuration, licensing & Turn-over Documents	20,000.00	
VHF Antenna (Bands: Tunable from 144-174/ Gain dB: 7.8)				
2	set	DIAMOND WHIP ANTENNA 1. Antenna VHF Base, 144 to 174 MHz, Power Max 200 Watt, Length 460 cm, Gain 7.8dB. 2. Connector UHF-Female	8,700.00	
IP PABX				
		1) Main CPU: Cortex A8 600 MHz 2) Power Input: 100 V AC to 130 V AC: 2.2 A/200 V AC to 240 V AC: 1.3 A; 50 Hz/60 Hz 3) Power Consumption (when fully mounted): 110 W 4) Memory Backup Duration: 7 years 5) External Backup Battery: External battery port is supported. 6) Dialing • Trunk: Dial Pulse (DP) 10 pps, 20 pps Tone (DTMF) Dialling • Extension: Dial Pulse (DP) 10 pps, 20 pps Tone (DTMF) Dialling		

1	unit	<ul style="list-style-type: none"> 7) Mode Conversion: DP-DTMF, DTMF-DP 8) Ring Frequency: 20 Hz/25 Hz (selectable) 9) Operating Environment <ul style="list-style-type: none"> • Temperature: 0 °C to 40 °C • Humidity: 10 % to 90 % (non-condensing) 10) Conference Call Trunk: 32 parties (default)/96 parties (DSP installed), (10 x 3-party conference call, 12 x 8-party conference call, etc.) – 11) Music on Hold (MOH): Maximum 8 ports (Level Control: -31.5 dB to +31.5 dB per 0.5 dB), MOH: Selectable Internal/External Music Source Port 12) External Paging: Maximum 6 ports (Volume Control: -15.5 dB to +15.5 dB per 0.5 dB) 13) LAN Port 1: (for LAN connection) 10BASE-T/100BASE-TX (Auto MDI/MDI-X) 14) Extension Connection Cable: <ul style="list-style-type: none"> • SLT: 1-pair wire (T, R) • DPT: 1-pair wire (D1, D2) • APT: 2-pair wire (T, R, D1, D2) • PT-interface CS: 1-pair wire (D1, D2) • PT-interface CS (High-density): 4-pair wire (D1, D2) • DSS Console and Add-on Key Module: 1-pair wire (D1, D2) 15) Air-cooling Method: Fan 16) Dimension: 430 mm (W) x 367 mm (D) x 88 mm (H) 17) Weight (when fully mounted): Under 4.5 kg 	85,000.00	
units IP Desktop Phone				
2	unit	<ul style="list-style-type: none"> 1) 2 SIP accounts 2) 132 x 64 pixel 2.3-inch graphical LCD with backlight 3) HD Voice (G.722) 4) Up to 500 phonebook 5) 3-way conference call support 6) Compatible with Broadsoft UC one 7) 2 x 10/100M ports, PoE 8) Low standby power consumption 9) XML Application Interface 10) 2 Programmable keys / Line keys 11) Plug and Play configuration 12) Changeable angle stand 13) Wall mounting (Optional) 	5,000.00	

Brand Name:

Delivery Period:

Price Validity:

After having carefully read and accepted for General Conditions, I/We quote on the item at prices noted above.

Gundran-Radio
RFQ-NP-SVP-re-169-2022
Resolution No. 197 s. 2022
PR No. 202202-188

Tel. #./address/e-mail add

Date

C.M. Recto Avenue, Lapasan, Cagayan de Oro City 9000 Philippines, Tel. Nos. +63 (88) 856 1738; Telefax +63 (88) 856 4696 | www.ustp.edu.ph